



TECHNICAL SPECIFICATIONS

Product Range	Altitude
Product Description	Tufted Multi-Level Loop Carpet Tile
Yarn / Fibre	100% Solution Dyed Nylon
Machine Gauge	1/12th
Pile Height	4mm +/-0.5mm
Total Thickness	7mm +/-0.5mm
Tile Size	50cm x 50cm
Backing Structure	PVC with Recycled Content / Felt Backing
Tile Installation Method	Quarter Turn, Brick, Ashlar

SUSTAINABILITY SPECIFICATIONS

Less Waste	Modular carpet creates 85 – 90% less waste than broadloom carpet
Product Stewardship	100% take back & repurpose through accredited partner
Recycled Content	Minimum of 55% recycled content in the backing structure
	Average of 40% recycled content by weight of product

PERFORMANCE SPECIFICATIONS

Area of Use **Dimensional Stability Biocontaminant Control** Anti-Static Warranty

 $\begin{array}{c} \rightarrow \uparrow & \uparrow \uparrow \\ \uparrow & \rightarrow \end{array}$

Commercial Less than 0.2% variation Ultra Fresh Anti-microbial treated AATCC134 < 3000 Volts 15 year limited warranty: Manufacturing defect

- Dimensional stability
- Electrostatic propensity



Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.



AIRLAY FLOORCOVERINGS Head Office: 25-27 Lakeside Drive Broadmeadows, VIC 3047 Phone: (03) 9359 4705 Email: sales@airlay.com.au

WWW.AIRLAY.COM.AU